

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 3/14/95	3. REPORT TYPE AND DATES COVERED Annual Technical 2/1/94 - 1/31/95																			
4. TITLE AND SUBTITLE Interferometric Measurement with Squeezed Light			5. FUNDING NUMBERS N00014-92-J-1302 3108133-04 4124133-01																			
6. AUTHOR(S) Prof. Hermann Haus																						
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Research Laboratory of Electronics Massachusetts Institute of Technology 77 Massachusetts Avenue Cambridge, MA 02139			8. PERFORMING ORGANIZATION REPORT NUMBER																			
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Department of the Navy Office of Naval Research 800 North Quincy Street Arlington, VA 22217-5000			10. SPONSORING/MONITORING AGENCY REPORT NUMBER																			
11. SUPPLEMENTARY NOTES The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.																						
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE																			
13. ABSTRACT (Maximum 200 words) The work of Prof. Haus and his collaborators is summarized here &I <table border="1" style="float: right;"> <tr> <td colspan="2">For</td> </tr> <tr> <td>DTIC TAB</td> <td><input checked="" type="checkbox"/></td> </tr> <tr> <td>Unannounced</td> <td><input type="checkbox"/></td> </tr> <tr> <td>Justification</td> <td></td> </tr> <tr> <td colspan="2">By _____</td> </tr> <tr> <td colspan="2">Distribution / _____</td> </tr> <tr> <td colspan="2">Availability Codes</td> </tr> <tr> <td>Dist</td> <td>Avail and/or Special</td> </tr> <tr> <td>A-1</td> <td></td> </tr> </table>					For		DTIC TAB	<input checked="" type="checkbox"/>	Unannounced	<input type="checkbox"/>	Justification		By _____		Distribution / _____		Availability Codes		Dist	Avail and/or Special	A-1	
For																						
DTIC TAB	<input checked="" type="checkbox"/>																					
Unannounced	<input type="checkbox"/>																					
Justification																						
By _____																						
Distribution / _____																						
Availability Codes																						
Dist	Avail and/or Special																					
A-1																						
14. SUBJECT TERMS			15. NUMBER OF PAGES																			
			16. PRICE CODE																			
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL																			

19950322 095

Annual Technical Report for the Office of Naval Research
Grant No. N00014-92-J-1302

Interferometric Measurement with Squeezed Light

Principal Investigator: Professor Hermann A. Haus
Graduate Students: Keren Bergman and Luc Boivin

The goal of the project is to develop interferometric measurement methods, using squeezed light, with noise levels below the "standard quantum limit." The "standard quantum limit" is the shot noise level. If squeezed radiation is injected into the, normally, unexcited port of a Mach-Zehnder interferometer, the phase shift of the interferometer can be measured in a noise background that is below the shot noise level. In past experiments performed at 1.3μ wavelength using a nonlinear Sagnac loop^[1,2] we have demonstrated shot noise reduction of -5.1 dB ^[2]. In a phase measurement with a Mach-Zehnder interferometer we have achieved a noise level 3 dB below the shot noise level^[3]. In this measurement the losses of the bulk- (rather than fiber-) interferometer prevented the full utilization of the 5.1 dB shot noise reduction.

It is our present goal to achieve improved noise performance by increased noise reduction below the shot noise level. This will be done in a set-up operating in the 800 nm regime with a Ti:Sapphire laser source. In this wavelength regime we can count on higher quantum efficiencies of the photodetectors. The fiber losses are, of course, greater, but in short fiber systems these losses are still acceptably low. The dispersion is positive and squeezing of solitons is out of question. However, theoretical studies have shown^[4] that positive dispersion can be beneficial in achieving higher degrees of squeezing compared to the dispersion-free squeezing of Gaussian pulses at 1.3μ .

In the past year we have built up a Ti:Sapphire based system using short (subpicosecond) pulses at 70 MHz repetition rate. We are still attempting to perfect a source with a 1 GHz repetition rate to overcome the Guided Acoustic Wave Brillouin Scattering (GAWBS) noise problem^[5], but have not yet succeeded in reducing its amplitude fluctuations to acceptable levels. In the meantime we intend to perform squeezing experiments with short fibers and short pulses of high peak intensity using the 70 MHz source. This is an alternate way of reducing the GAWBS noise effect^[6]. The squeezing system is self-stabilized by provided the same optical paths for the local oscillator pump and squeezed radiation^[7].

We have resolved some important theoretical issues.

1. When short pulses are used for squeezing, the finite response time of the Kerr medium must be taken into account. Further, some additional terms appear in the nonlinear Schrödinger equation which, upon quantization, do not preserve the commutators of the electric field operators. The violation of the commutator relations from the finite response time of the Kerr effect was resolved last year by constructing a self-consistent model of the Kerr effect^[8]. The appropriate noise sources that prevent the

violation of commutator conservation have been determined. The additional terms, which arise from the rapid variation of the envelope, cause similar violations. We have determined the sources necessary to render the equations self-consistent.

2. The use of positive dispersion for squeezing complicates the problem in that the pulse changes shape while modulating the noise. We have made a full analysis of the squeezing process and found that higher degrees of squeezing can be obtained with positive dispersion than at zero dispersion or with squeezing of solitons with negative dispersion^[4]. We found that there is a great deal of coherence across the entire pulse profile. Thus, if detection is with a local oscillator pulse much shorter than the squeezing pulse (windowing), the noise reduction is small or nonexistent. Only when the entire pulse is used as the local oscillator pulse can one achieve appreciable noise reduction^[9].
3. Using a computer simulation we have determined the squeezing in a Sagnac interferometer at zero dispersion without any approximations (fully nonlinear analysis)^[10].
4. Solitons permit a particularly simple description of squeezing. Following up on previous work on soliton squeezing^[11], we have investigated the nature of minimum uncertainty excitations of solitons. We have determined the conditions under which the phase and amplitude of a soliton meets the minimum uncertainty condition, and the alternate case when the minimum uncertainty condition is obeyed, instant by instant, across the envelope of the soliton (under the Slowly Varying Envelope approximation)^[12].
5. A complete analysis of the Raman effect on squeezing of cw light (or a square pulse) has been carried out^[13].

References

- [1] M. Shirasaki and H. A. Haus, "Squeezing of pulses in a nonlinear interferometer," *J. Opt. Soc. Am. B* **7**, 30-34, Jan. 1990.
- [2] K. Bergman and H. A. Haus, "Squeezing in fibers with optical pulses," *Opt. Lett.* **16**, 663-665, May 1991; K. Bergman, H. A. Haus, E. P. Ippen, and M. Shirasaki, "Squeezing in a fiber interferometer with a gigahertz pump," *Opt. Lett.* **19**, 290-292, February 1994
- [3] K. Bergman, C. R. Doerr, H. A. Haus, and M. Shirasaki, "Sub-shot-noise measurement with fiber-squeezed optical pulses," *Opt. Lett.* **18**, 643-645, Apr. 1993.
- [4] C. R. Doerr, F. I. Khatri, and M. Shirasaki, "Simulation of pulsed squeezing in optical fiber with chromatic dispersion," *J. Opt. Soc. Am. B* **11**, 143-149, January 1994.

- [5] R. H. Shelby, M. D. Levenson, and P. W. Bayer, "Guided acoustic-wave Brillouin scattering," *Phys. Rev. B* **31**, 5244-5252, April 1985.
- [6] C. R. Doerr, I. Lyubomirsky, G. Lenz, J. Paye, H. A. Haus, and M. Shirasaki, "Optical squeezing with a stretched fiber," *QELS'93 Technical Digest* **12**, p. 281 (1993).
- [7] M. Shirasaki, C. R. Doerr, K. Bergman, and H. A. Haus, "Optical squeezing with self-phase-stabilized scheme," in *Nonlinear Optics: Materials, Fundamentals, and Applications Technical Digest* **18**, Optical Society of America, Washington, DC, 173-175 (1992).
- [8] L. Boivin, F. X. Kartner, and H. A. Haus, "Analytical solution to the quantum field theory of self phase modulation with a finite response time," *Phys. Rev. Lett.* **73**, 240 (1994); L. Boivin, F. X. Kartner, and H. A. Haus, "Quantum theory of SPM with finite theory of self phase modulation with a finite response time," in *Technical Digest of the International Quantum Electronics Conference*, Anaheim, CA, 1994, p. 200.
- [9] L. Boivin, C. R. Doerr, K. Bergman, and H. A. Haus, "Quantum noise reduction using a nonlinear Sagnac loop with positive dispersion," in the *Proceedings of the Workshop on Quantum Communication and Measurements*, Nottingham, England, 1995, p. 489.
- [10] L. Boivin, "The Sagnac loop squeezer at zero dispersion with a finite response time for the Kerr nonlinearity," *Phys. Rev. A*, submitted for publication.
- [11] Y. Lai and H. A. Haus, "Quantum theory of solitons in optical fibers. I. Time-dependent Hartree approximation," *Phys. Rev. A* **40**, 844-853, July 1989; Y. Lai and H. A. Haus, "Quantum theory of solitons in optical fibers. II. Exact solution," *Phys. Rev. A* **40**, 854-866, July 1989; H. A. Haus and Y. Lai, "Quantum theory of soliton squeezing— a linearized approach," *J. Opt. Soc. Am. B* **7**, 386-392, March 1990.
- [12] F. X. Kartner and L. Boivin, "Noise of the fundamental soliton, *Phys. Rev. A*, submitted for publication.
- [13] J. H. Shapiro and L. Boivin, "Raman noise limit on squeezing in continuous wave four-wave mixing," *Opt. Lett.*, in press.

Office of Naval Research

DISTRIBUTION LIST

Herschel S. Pilloff
Scientific Officer

3 copies

Code: 1112L0
Office of Naval Research
800 North Quincy Street
Arlington, VA 22217

Administrative Contracting Officer
E19-628
Massachusetts Institute of Technology
Cambridge, MA 02139

1 copy

Director
Naval Research Laboratory
Washington, DC 20375
Attn: Code 2627

1 copy

Defense Technical Information Center
Bldg. 5, Cameron Station
Alexandria, VA 22314

2 copies